


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62283040/WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2918.8 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1820	1812	1809	1810	1815	1824	1829	1828	0- 10	176.9	176.9	6.06
20	1628	1616	1608	1610	1625	1636	1643	1644	10- 20	487.7	664.7	22.8
30	1273	1253	1247	1254	1277	1296	1304	1298	20- 30	676.7	1341	46
40	784.4	767.2	760.6	770.2	794.5	808.1	818.9	812.1	30- 40	642.4	1984	68
50	395.1	381.2	380.7	387.0	396.3	411.0	415.4	408.0	40- 50	445.5	2429	83.2
60	186.9	183.4	181.0	184.6	187.6	191.3	190.8	191.2	50- 60	248.5	2678	91.7
70	112.1	107.6	103.6	108.8	112.9	111.6	108.2	111.8	60- 70	144.6	2822	96.7
80	46.20	40.18	35.47	41.06	44.61	43.76	40.23	44.17	70- 80	78.79	2901	99.4
90	0.7734	0.7496	0.7243	0.7642	0.6838	0.6734	0.6672	0.6756	80- 90	17.73	2919	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:06 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

