

The Brand of Electricity

LED GROUND FIXTURE GRFLED068



TECHNICAL SPECIFICATION

FACADE AND GROUND



Technical data:

Rated voltage: 100-240V / 50-60Hz

Power: 1.2WLED source: Epistar

Colour temperature: 6000-6500KMaterial: 304 Stainless steel

Body colour: GreyIK Rating: IK10Insulation class III


Protection against dust and moisture: IP67



Features:

- Modern and stylish design
- Durable in ground LED lights
- Made from 304 stainless steel, it is durable with a strong resistance to pitting and rusting.
- Corrosion proof
- Highly efficient replacement of conventional lighting fixtures
- Long-life and efficient
- Economic- low power consumption
- Environmentally friendly no mercury and lead
- Ideal for edging and highlighting areas of the garden such as decking, steps, and patio areas

Variants and Dimensions:




Catalogue number	Watt (W)	Whole fixture lumens (Im)	Colour temp. (K)	Colour	Size (mm)		Beam angle	Packing /Box (pcs)
					Diameter	Height		
96GRFLED068	1.2	35	6000-6500	grey	100	61	45°	1/40

TECHNICAL SPECIFICATION

FACADE AND GROUND





EN 55015 • EN 61000-3-2 • EN 61000-3-3 • EN 61547 • EN 60598-1 • EN 60598-2-2 • EN 13032-4

