


LAMP PHOTOMETRIC REPORT

MODEL: 99PFML30/WH		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1194.5 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	433.0	432.7	436.7	432.9	432.5	431.7	431.4	431.5	0- 10	41.79	41.79	3.5
20	401.0	402.0	402.5	404.6	402.4	400.2	399.7	400.0	10- 20	118.2	160.0	13.4
30	354.5	356.5	369.1	374.4	367.5	352.6	352.6	352.8	20- 30	176.3	336.3	28.2
40	297.7	318.9	306.8	314.6	314.1	294.4	293.5	294.9	30- 40	208.5	544.8	45.6
50	251.8	249.4	239.1	257.7	249.1	230.9	229.8	231.7	40- 50	212.3	757.1	63.4
60	184.4	184.9	172.7	186.0	187.1	165.8	164.5	166.3	50- 60	188.2	945.2	79.1
70	115.7	115.8	112.3	114.6	120.2	101.9	100.7	102.3	60- 70	141.7	1087	91
80	49.89	52.42	51.13	53.69	50.09	43.40	42.85	43.92	70- 80	83.43	1170	98
90	3.877	1.300	13.14	1.778	4.255	0.9468	0.6592	0.9409	80- 90	24.13	1194	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:16 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

MODEL: 99PFML30/WH		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

UNIT: cd

[illegible]

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```