


LAMP PHOTOMETRIC REPORT

MODEL: 99POM1505040/WH		
POWER: 50W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5208.5 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1988	1997	1998	1983	1979	1984	1998	1999	0- 10	192.4	192.4	3.69
20	1833	1861	1874	1835	1817	1838	1875	1865	10- 20	544.2	736.5	14.1
30	1596	1648	1681	1613	1576	1616	1679	1653	20- 30	805.7	1542	29.6
40	1304	1376	1429	1336	1281	1339	1427	1383	30- 40	938.4	2481	47.6
50	997.2	1071	1138	1030	974.2	1033	1137	1078	40- 50	933.5	3414	65.6
60	695.6	760.0	827.7	720.1	670.1	723.4	826.8	766.8	50- 60	807.4	4222	81.1
70	402.9	455.9	516.0	419.2	379.7	422.4	518.0	461.9	60- 70	590.2	4812	92.4
80	140.2	177.8	226.5	147.7	122.0	150.3	228.2	182.8	70- 80	321.9	5134	98.6
90	2.752	3.940	3.482	2.883	2.063	2.516	3.133	4.316	80- 90	74.72	5208	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 01 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:


```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```